

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Mintex Brake Fluid DOT 3

Product code:

MBF3-1000B

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Hydraulic (functional) fluids
PC-TEC-8: Hydraulic fluids, including brake and transmission fluids**1.3. Details of the supplier of the safety data sheet**

Company name:	TMD Friction Services GmbH	
Street:	Schlebuscher Str. 99	
Place:	D-51381 Leverkusen	
Telephone:	+49 (2171)703-0	
E-mail:	serviceline@tmdfriction.com	
Contact person:	Hr. Beier	Telephone: +49 (2171)9113-7373
E-mail:	serviceline@tmdfriction.com	
Internet:	www.tmdfriction.com	

1.4. Emergency telephone number:

GIZ Bonn: +49 (0)228-19240 (24/7)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**Eye Irrit. 2; H319
Repr. 2; H361fd

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Signal word: Warning**Pictograms:****Hazard statements**H319 Causes serious eye irritation.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.**Precautionary statements**P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves and eye/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 2 of 11

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This material is combustible, but will not ignite readily.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol			25 - < 30 %
	205-592-6	603-183-00-0	01-2119475107-38	
	Eye Dam. 1; H318			
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			15 - 25 %
	250-418-4		01-2119462824-33	
	Repr. 2; H361fd			
111-46-6	2,2'-oxybisethanol; diethylene glycol			10 - 15 %
	203-872-2	603-140-00-6	01-2119457857-21	
	Acute Tox. 4; H302			
1559-34-8	3,6,9,12-tetraoxahexadecan-1-ol			5 - 10 %
	216-322-1			
	Eye Irrit. 2; H319			
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			1 - 3 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			
111-77-3	2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether			< 0,25 %
	203-906-6	603-107-00-6	01-2119475100-52	
	Repr. 1B; H360D			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
143-22-6	205-592-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol	25 - < 30 %
	Eye Dam. 1; H318: >= 30 - 100 Eye Irrit. 2; H319: >= 20 - < 30		
111-46-6	203-872-2	2,2'-oxybisethanol; diethylene glycol	10 - 15 %
	oral: ATE = 500 mg/kg		
111-77-3	203-906-6	2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether	< 0,25 %
	Repr. 1B; H360D: >= 3 - 100		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 3 of 11

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

Clean with detergents. Avoid solvent cleaners.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Immediately call a doctor.

Following ingestion large scale (Manufacturer): Immediately call a doctor. Alcohol (40 %) 90 - 120 mL (2 mg/kg bw)

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water mist, alcohol resistant foam, Dry extinguishing powder, Carbon dioxide (CO₂).
Co-ordinate fire-fighting measures to the fire surroundings.**Unsuitable extinguishing media**

Full water jet

5.2. Special hazards arising from the substance or mixture

This material is combustible, but will not ignite readily.

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂), Pyrolysis products, toxic.**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. Evacuate area. Remove persons to safety. Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 4 of 11

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Clean with detergents. Avoid solvent cleaners.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol. Wear personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep only in the original container. Keep locked up. Store in a place accessible by authorized persons only.

Hints on joint storage

Do not store together with: Acid, alkali (Base), Oxidising agent, Reducing agent.

Further information on storage conditions

Keep away from heat.

storage temperature: 15 - 30 °C

7.3. Specific end use(s)

Hydraulic (functional) fluids

PC-TEC-8: Hydraulic fluids, including brake and transmission fluids

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	
		15	101.2		STEL (15 min)	
111-77-3	2-(2-Methoxyethoxy)ethanol	10	50.1		TWA (8 h)	
111-46-6	Diethylene glycol	23	100		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 5 of 11

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol			
Worker DNEL, long-term		dermal	systemic	50 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	195 mg/m ³
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			
Worker DNEL, long-term		dermal	systemic	8,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,1 mg/m ³
111-46-6	2,2'-oxybisethanol; diethylene glycol			
Worker DNEL, long-term		dermal	systemic	43 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	44 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			
Worker DNEL, long-term		dermal	systemic	20 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	67 mg/m ³
111-77-3	2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether			
Worker DNEL, long-term		dermal	systemic	2,22 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	50,1 mg/m ³

PNEC values

CAS No	Substance	Value
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol	
Micro-organisms in sewage treatment plants (STP)		200 mg/l
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
Micro-organisms in sewage treatment plants (STP)		100 mg/l
111-46-6	2,2'-oxybisethanol; diethylene glycol	
Micro-organisms in sewage treatment plants (STP)		199,5 mg/l
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	
Micro-organisms in sewage treatment plants (STP)		200 mg/l
111-77-3	2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether	
Micro-organisms in sewage treatment plants (STP)		10000 mg/l

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Eye glasses with side protection (EN 166)

Hand protection

Wear suitable gloves tested to EN374.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 6 of 11

penetration time (maximum wearing period): > 480 min.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of glove material: 0,3 mm

Suitable material: NBR (Nitrile rubber)

Thickness of glove material: 0,2 mm

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	amber
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	< -50 °C
Boiling point or initial boiling point and boiling range:	> 210 °C
Flammability:	This material is combustible, but will not ignite readily.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	> 100 °C
Auto-ignition temperature:	> 280 °C
Decomposition temperature:	300 °C
pH-Value:	7 - 10,5
Viscosity / kinematic: (at 20 °C)	5 - 10 mm ² /s
Water solubility:	easily soluble
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	1,50
Vapour pressure: (at 20 °C)	1,0 hPa
Density:	1,01 - 1,06 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Other safety characteristics**

Evaporation rate: (n-Butyl acetate=100) 0,01

Further Information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 7 of 11

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Acid, alkali (Base), Oxidising agent, Reducing agent.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂), Pyrolysis products, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Absorption large scale (Manufacturer): May cause damage to organs. (kidneys)

ATEmix tested

	Dose	Species	Source
LD50, oral	> 5000 mg/kg	Rat	Manufacturer
LD50, dermal	> 3000 mg/kg	Rabbit	Manufacturer

ATEmix calculated

ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-46-6	2,2'-oxybisethanol; diethylene glycol				
	oral	ATE 500 mg/kg			

Information on likely routes of exposure

oral, Skin contact, Eye contact, Inhalation.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Absorption large scale (Manufacturer)

The following symptoms may occur: Depression of central nervous system, kidneys Gastrointestinal complaints, Headache, Nausea.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 8 of 11

12.2. Persistence and degradability

Product is biodegradable. (OECD 302B)

12.3. Bioaccumulative potential

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

12.4. Mobility in soil

Soluble in: Water. If product enters soil, it will be mobile and may contaminate groundwater.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 9 of 11

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 54, Entry 55, Entry 75

Directive 2010/75/EU on industrial emissions: < 26 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 7,9,11,12,15,16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 10 of 11

Abbreviations and acronyms

Acute Tox: Acute toxicity
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 Repr: Reproductive toxicity
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 M-Factor: Multiplication Factor
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 TI: Technical Instructions
 DGR: Dangerous Goods Regulations
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 EG or EC: European Community
 IE: Industrial Emissions
 SVHC: Substance of Very High Concern

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361fd	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
 H318 Causes serious eye damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Mintex Brake Fluid DOT 3

Revision date: 28.02.2024

Page 11 of 11

H319	Causes serious eye irritation.
H360D	May damage the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)