

Telephone: +49 (2171)9113-7373

Safety Data Sheet

according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Textar Brake Fluid DOT 5.1

Product code:

95006600

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic (functional) fluids

PC-TEC-8: Hydraulic fluids, including brake and transmission fluids

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: TMD Friction Services GmbH

Street: Schlebuscher Str. 99
Place: D-51381 Leverkusen
Telephone: +49 (2171)703-0

E-mail: serviceline@tmdfriction.com

Contact person: Hr. Beier

E-mail: serviceline@tmdfriction.com

Internet: www.tmdfriction.com

Supplier

Company name: TMD Friction UK Ltd Street: 46-47, Hardwick Grange

Place: Woolston, Warrington WA1 4RF

Telephone: 03300 583908

1.4. Emergency telephone GIZ Bonn: +49 (0)228-19240 (24/7)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319 Repr. 2; H361fd

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Signal word: Warning

Pictograms:





Hazard statements

H319 Causes serious eye irritation.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.





according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 2 of 11

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves and eye/face protection.
P308+P313 Wear protective gloves and eye/face protection.
IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This material is combustible, but will not ignite readily.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

Chemical name			Quantity
EC No	Index No	REACH No	
Classification (GB CLP Regula	tion)		
Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			80 - 95 %
250-418-4		01-2119462824-33	
Repr. 2; H361fd			
		ycol monobutylether; butoxytriethylene	10 - 15 %
205-592-6	603-183-00-0	01-2119475107-38	
Eye Dam. 1; H318			
3,6,9,12-tetraoxahexadecan-1-ol			1 - 3 %
216-322-1			
Eye Irrit. 2; H319			
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether		< 1 %	
203-961-6	603-096-00-8	01-2119475104-44	
Eye Irrit. 2; H319			
2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether		ether	< 1 %
203-906-6	603-107-00-6	01-2119475100-52	
Repr. 1B; H360D			
	EC No Classification (GB CLP Regular Tris[2-[2-(2-methoxyethoxy)eth 250-418-4 Repr. 2; H361fd 2-[2-(2-butoxyethoxy)ethoxy]eti glycol 205-592-6 Eye Dam. 1; H318 3,6,9,12-tetraoxahexadecan-1- 216-322-1 Eye Irrit. 2; H319 2-(2-butoxyethoxy)ethanol; diet 203-961-6 Eye Irrit. 2; H319 2-(2-methoxyethoxy)ethanol; diet 203-906-6	EC No Classification (GB CLP Regulation) Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate 250-418-4 Repr. 2; H361fd 2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene gliglycol 205-592-6 Eye Dam. 1; H318 3,6,9,12-tetraoxahexadecan-1-ol 216-322-1 Eye Irrit. 2; H319 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl eth 203-961-6 Eye Irrit. 2; H319 2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl 203-906-6 603-107-00-6	EC No

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
143-22-6	205-592-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol	10 - 15 %
	Eye Dam. 1; H	318: >= 30 - 100 Eye Irrit. 2; H319: >= 20 - < 30	
111-77-3	203-906-6	2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether	< 1 %
	Repr. 1B; H36	0D: >= 3 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet



according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 3 of 11

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

Clean with detergents. Avoid solvent cleaners.

After contact with eves

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Immediately call a doctor.

Following ingestion large scale (Manufacturer): Immediately call a doctor. Alcohol (40 %) 90 - 120 mL (2 mg/kg bw)

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, alcohol resistant foam, Dry extinguishing powder, Carbon dioxide (CO2).

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

This material is combustible, but will not ignite readily.

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Evacuate area. Remove persons to safety. Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Use personal protection equipment.

For emergency responders

Use personal protection equipment.





according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 4 of 11

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Clean with detergents. Avoid solvent cleaners.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol. Wear personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

Do not store together with: Acid, alkali (Base), Oxidising agent, Reducing agent.

Further information on storage conditions

Keep away from heat.

storage temperature: 15 - 30 °C

7.3. Specific end use(s)

Hydraulic (functional) fluids

PC-TEC-8: Hydraulic fluids, including brake and transmission fluids

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Safety Data Sheet

according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 5 of 11

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
111-77-3	2-(2-Methoxyethoxy)ethanol	10	50.1		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			
Worker DNEL	, long-term	dermal	systemic	8,3 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	29,1 mg/m³
143-22-6	143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol			
Worker DNEL	, long-term	dermal	systemic	50 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	195 mg/m³
112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether				
Worker DNEL	, long-term	dermal	systemic	20 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	67 mg/m³
111-77-3	2-(2-methoxyethoxy)ethanol; diethylene glycol monomet	hyl ether		
Worker DNEL	long-term	dermal	systemic	2,22 mg/kg bw/day
Worker DNEL	long-term	inhalation	systemic	50,1 mg/m³

PNEC values

CAS No	Substance		
Environmental compartment Value		Value	
30989-05-0	30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate		
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol; TEGBE; triethylene glycol monobutylether; butoxytriethylene glycol		
Micro-organisms in sewage treatment plants (STP) 200 mg/l		200 mg/l	
112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			
Micro-organisms in sewage treatment plants (STP) 200 mg/l		200 mg/l	
111-77-3 2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether			
Micro-organisms in sewage treatment plants (STP) 10000 mg/l			

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Eye glasses with side protection (EN 166)



according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 6 of 11

Hand protection

Wear suitable gloves tested to EN374.

penetration time (maximum wearing period): > 480 min. Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of glove material: 0,3 mm Suitable material: NBR (Nitrile rubber) Thickness of glove material: 0,2 mm

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

amber

characteristic

not applicable

Melting point/freezing point: < -50 °C
Boiling point or initial boiling point and > 260 °C

boiling range:

Flammability: This material is combustible, but will not ignite

readily.

(at 20 °C)
Water solubility:
easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: 1,50
Vapour pressure: 1,00 hPa

(at 20 °C)

Density: 1,02 - 1,07 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Other safety characteristics

Print date: 04.03.2024

Safety Data Sheet

according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 7 of 11

Evaporation rate: (n-Butyl acetate=100) 0,01

Further Information
Wet boiling point: < 165 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Acid, Strong alkali, Oxidizing agents, strong. Reducing agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Pyrolysis products, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Absorption large scale (Manufacturer): May cause damage to organs. (kidneys)

ATEmix tested

LD50, oralDoseSpeciesSourceLD50, dermal> 5000 mg/kgRatManufacturerLD50, dermal> 3000 mg/kgRabbitManufacturer

ATEmix calculated

ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility. Suspected of damaging the unborn child. (Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation, Skin contact, Eye contact, oral



according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 8 of 11

Practical experience

Absorption large scale (Manufacturer)

The following symptoms may occur: Depression of central nervous system, Gastrointestinal complaints, Headache, Nausea

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Absorption large scale (Manufacturer)

The following symptoms may occur: Depression of central nervous system, Gastrointestinal complaints, Headache, Nausea.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

12.2. Persistence and degradability

Product is biodegradable. (OECD 302B)

12.3. Bioaccumulative potential

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

12.4. Mobility in soil

Soluble in: Water. If product enters soil, it will be mobile and may contaminate groundwater.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Print date: 04.03.2024

Safety Data Sheet

according to UK REACH Regulation

Textar Brake Fluid DOT 5.1 Revision date: 01.03.2024 Page 9 of 11

No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): 14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 30, Entry 54, Entry 75

Directive 2010/75/EU on industrial < 95 %

emissions:

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,7,9,11,15,16.



according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 10 of 11

Abbreviations and acronyms

Eye Dam: Eye damage Eye Irrit: Eye irritation Repr: Reproductive toxicity

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways CLP:

Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
M-Factor: Multiplication Factor
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide



Print date: 04.03.2024

Safety Data Sheet

according to UK REACH Regulation

Textar Brake Fluid DOT 5.1

Revision date: 01.03.2024 Page 11 of 11

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

TI: Technical Instructions

DGR: Dangerous Goods Regulations

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds EG or EC: European Community

IE: Industrial Emissions

SVHC: Substance of Very High Concern

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361fd	Calculation method

Relevant H and EUH statements (number and full text)

H318 Causes serious eye damage. H319 Causes serious eye irritation. H360D May damage the unborn child.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)