

# Safety Data Sheet

according to GSO ISO 11014:2013

**TEXTAR**  
BRAKE TECHNOLOGY

## Textar FORMULA XT

Revision date: 21.10.2021

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Textar FORMULA XT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cleaning agent

#### 1.3. Details of the supplier of the safety data sheet

Company name:	TMD Friction Services GmbH	
Street:	Schlebuscher Str. 99	
Place:	D-51381 Leverkusen	
Telephone:	+49 (2171)703-0	
e-mail:	serviceline@tmdfriction.com	
Contact person:	Hr. Beier	Telephone: +49 (2171)9113-7373
e-mail:	serviceline@tmdfriction.com	
Internet:	www.tmdfriction.com	

#### 1.4. Emergency telephone number:

GIZ Bonn: +49 (0)228-19240 (24/7)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### UN-GHS (ST/SG/AC.10/30/Rev.5)

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### UN-GHS (ST/SG/AC.10/30/Rev.5)

##### Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)

Signal word: Danger

Pictograms:



##### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 2 of 10

H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe Aerosol.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of waste according to applicable legislation.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.  
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	GHS Classification	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)	95 - <= 100 %
	921-024-6	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a doctor.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms can occur only after several hours.  
Headache, Dizziness, Fatigue, Causes skin irritation.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 3 of 10

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water mist, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.  
Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>), aldehydes, carbon black, Pyrolysis products, toxic.

### 5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 4 of 10

### Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Heating causes rise in pressure with risk of bursting. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol.

### Further information on handling

Do not pierce or burn, even after use.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.  
Keep away from food, drink and animal feedingstuffs.

#### Further information on storage conditions

Protect against: frost. Keep away from heat. Protect against direct sunlight.

### 7.3. Specific end use(s)

Cleaning agent

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### (OSHA-SF) Occupational Standards and Value Guidelines (Version 3.0)

Oil mist (mineral) mildly refined:

TWA: 0,2 mg/m<sup>3</sup>

Carbon dioxide (CAS: 124-38-9):

TWA: 5000 ppm 9000 mg/m<sup>3</sup>

STEL: 30000 ppm 45000 mg/m<sup>3</sup>

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye protection/face protection. Eye glasses with side protection (DIN EN 166)

##### Hand protection

Wear suitable gloves tested to EN374.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: NBR (Nitrile rubber) penetration time (maximum wearing period): > 480 min.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 5 of 10

Thickness of glove material: 0,45 mm

### Skin protection

Wear suitable protective clothing.

### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation, Vapour, exceeding exposure limit values.

Suitable respiratory protection apparatus: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

### Environmental exposure controls

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid (Aerosol)

Colour: colourless

Odour: like: Solvents

Odour threshold: not applicable

#### Changes in the physical state

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling range: 88 °C

Sublimation point: not determined

Softening point: not determined

Flash point: -12 °C

#### Flammability

Solid/liquid: not applicable

Gas: not applicable

#### Explosive properties

Heating may cause an explosion. Vapours can form explosive mixtures with air.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 7,2 vol. %

Auto-ignition temperature: not determined

#### Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

The product is not: oxidising.

pH-Value: not applicable

Viscosity / dynamic: not determined

Viscosity / kinematic: < 7 mm<sup>2</sup>/s

Water solubility: practically insoluble

#### Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 6 of 10

Vapour pressure: not determined  
Density (at 20 °C): 0,714 g/cm<sup>3</sup>  
Relative vapour density: not determined

### 9.2. Other information

#### Other safety characteristics

Solvent separation test: not determined  
Evaporation rate: not determined

#### Further Information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Heating causes rise in pressure with risk of bursting.  
Vapours can form explosive mixtures with air.

### 10.4. Conditions to avoid

Do not expose to temperatures above 50 °C. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.  
Protect against: frost. Keep away from heat. Protect against direct sunlight.

### 10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>), aldehydes, carbon black, Pyrolysis products, toxic.

#### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### Information on Toxicological Effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Manufacturer	

#### Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 7 of 10

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0))

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

oral, dermal, inhalative, Eye contact.

## 11.2. Information on other hazards

### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)					
	Acute fish toxicity	LC50 mg/l	> 1 - 10	96 h	Pimephales promelas (fathead minnow)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Manufacturer OECD 201
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	Manufacturer

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)				
	OECD 301F	98 %	28	Manufacturer	
	Readily biodegradable (according to OECD criteria).				

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)	3,4 - 5,2

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 8 of 10

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Do not pierce or burn, even after use.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### UN Recommendations on the Transport of Dangerous Goods - Model Regulations

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

### Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1



Special Provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 1950
-------------------------	---------



# Safety Data Sheet

according to GSO ISO 11014:2013

## Textar FORMULA XT

Revision date: 21.10.2021

Page 9 of 10

**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)

### 14.6. Special precautions for user

Warning: Flammable gases, flammable liquids

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulatory information

Observe in addition any national regulations!

## SECTION 16: Other information

### Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienist

ATE: Acute toxicity estimate

BCF: Bio-concentration factor

CAS: Chemical Abstracts Service

DGR: Dangerous Goods Regulations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

EC50: Effective Concentration 50%

EL50: Effect loading, 50%

ErC50: Effective Concentration 50%, growth rate

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

IATA: International Air Transport Association

## Safety Data Sheet

according to GSO ISO 11014:2013



### Textar FORMULA XT

Revision date: 21.10.2021

Page 10 of 10

IBC: Intermediate Bulk Container  
ICAO: International Civil Aviation Organization  
IMDG: International Maritime Code for Dangerous Goods  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
NOEC: No Observed Effect Concentration  
OEL: Occupational Exposure Limit  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
STEL: Short-Term Exposure Limit  
TWA: Time weighted average  
UN: United Nations

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*